



MATERIAL SAFETY DATA SHEET

SECTION 1. Chemical Product and Company Identification			
Product Name:	Spray Dried Alumina Powder	Chemical Name:	Aluminum Oxide
Supplier:	Superior Technical Ceramics Corp. 600 Industrial Park Road St. Albans, VT 05478 (802) 527-7726 phone (802) 527-1181 fax	<u>In Case of Emergency Call:</u> (802) 527-7726	
Synonym:	"Ready to process" alumina powder (grades vary upon request).		
Material Use:	For forming pressed compacts and fired ceramic components.		
Date Prepared:	June 23, 2009		
Prepared By:	Janna L. Bevins/Brian H. Gold		

SECTION 2. Composition, Information or Ingredients			
NAME:	CAS#:	% BY WEIGHT	COMMENTS:
Aluminum Oxide	1344-28-1	Greater than 74	10 mg/m ³ TWA matter containing <1% crystalline silica.
Organic Binders		3-10	Proprietary, but not hazardous.
Oxide additives		0.2-26	Proprietary

SECTION 3. Hazards Identification			
Emergency Overview:			
Organic portion may be combustible. Dust may cause irritation to eyes, nose, throat, and/or skin.			
Health Rating:	Flammability Rating:	Reactivity Rating:	Contact Rating:
2 – Moderate	0 – None	0 – None	2 – Moderate
Lab Protective Equipment:	Eye protection and proper dust collection if machining occurs.		
Storage Color Code:	Green (General Storage)		
Potential Health Effects:			
Inhalation:	Hazard is principally that of a nuisance dust. Coughing or shortness of breath may occur in cases of excessive inhalation.		
Ingestion:	No adverse effects expected.		
Skin Contact:	No adverse effects expected but dust may cause irritation.		
Eye Contact:	No adverse effects expected but dust may cause irritation.		
Chronic Exposure:	No adverse effects expected.		
Aggravation of Pre-existing Conditions:	Not expected to be a health hazard.		



MATERIAL SAFETY DATA SHEET

SECTION 4. First Aid Measures	
Inhalation:	Move to fresh air and consult with local medical personnel if discomfort persists.
Ingestion:	Administer water to dilute, but not if person is unconscious. Consult with local medical personnel if discomfort persists.
Eye Contact:	Flush with tepid water for a minimum of 15 minutes and consult with local medical personnel if discomfort persists.
Skin Contact:	Wash affected area with soap and water and consult with local medical personnel if irritation persists.

SECTION 5. Fire-Fighting Measures	
Fire:	Possible Class A fire hazard – combustible vapors can develop in the headspace over the product. Flash point is 220°C (428°F).
Explosion:	Not considered an explosion hazard.
Fire Extinguishing Media:	Use any means suitable for extinguishing surrounding fire.
Special Information:	Use protective clothing and breathing equipment appropriate for the surrounding fire and to protect against the aluminum oxide dust that may be dispersed in the air.

SECTION 6. Accidental Release Measures	
Ventilate area of leak or spill and wear appropriate personal protective equipment as specified in Section 8. Sweep up any spills and place in containers for disposal or reclaim. Vacuuming or wet sweeping may be used to avoid excessive dust.	

SECTION 7. Handling and Storage	
Store in a cool dry place. Any dust should be sponge mopped.	

SECTION 8. Exposure Controls and Personal Protection	
Airborne Exposure Limits:	10 mg/m ³ TWA matter containing <1% crystalline silica.
Ventilation System:	Local or general exhaust ventilation recommended.
Personal Respirators (NIOSH Approved):	NIOSH/MSHA approved respirator for dust when exposure limit is exceeded.
Skin Protection:	Polymer gloves for prolonged dust exposure.
Eye Protection:	Safety goggles in the presence of airborne dust.



MATERIAL SAFETY DATA SHEET

SECTION 9. Physical and Chemical Properties			
Appearance:	White or Colored Flowable Powder	pH:	NIA
Odor:	Odorless	Boiling Point:	NIA
Solubility:	Organic Portion Soluble in Water	Melting Point:	1871-2038°C (3400-3700°F)
Specific Gravity:	>0.8 g/cc	Vapor Pressure/ Vapor Density:	NIA

SECTION 10. Stability and Reactivity					
Chemical Stability:	Stable				
Hazardous Decomposition:	CO and CO ₂ in a fire and at temperatures >220°C (428°F).				
Hazardous Polymerization:	NIA	Incompatibilities:	NIA	Conditions to Avoid:	NIA

SECTION 11. Toxicological Information
NIA

SECTION 12. Ecological Information
NIA

SECTION 13. Disposal Considerations
This material is not hazardous per 40 CFR 261. Consultation with federal, state and local officials is recommended before disposal.

SECTION 14. Transport Information
Not regulated.