



## Safety Data Sheet STC Type "B" Glass Coating Slurry

---

### SECTION 1: Identification

#### Product identifier

Product name STC Type "B" Glass Coating Slurry  
Other names / synonyms GLZ 4200 Aqueous Slurry, Glaze

#### Recommended use of the chemical and restrictions on use

Raw material for technical ceramic components.

#### Supplier's details

Name Superior Technical Ceramics  
Address 600 Industrial Park Road  
St. Albans, Vermont 05478  
USA

Telephone 802-527-7726  
Fax 802-527-1181

#### Emergency phone number(s)

802-527-7726

---

### SECTION 2: Hazard identification

#### Classification of the substance or mixture

- Carcinogenicity (chapter 3.6), Cat. 1
- Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 1

#### GHS label elements, including precautionary statements

#### Pictogram



#### Signal word

**Danger**

#### Hazard statement(s)

H335 May cause respiratory irritation  
H350i May cause cancer by inhalation.  
H372 Causes damage to organs through prolonged or repeated exposure

#### Precautionary statement(s)

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

# Safety Data Sheet

## STC Type "B" Glass Coating Slurry

P308+P313  
P314

IF exposed or concerned: Get medical advice/attention.  
Get medical advice/attention if you feel unwell.

### Other hazards which do not result in classification

This product has the potential of generating respirable dust during handling and machining. Dust may contain respirable crystalline silica. Prolonged or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of lung fibrosis are cough and breathlessness. Control and monitor occupational exposure to respirable crystalline silica dust in accordance to federal, state and local laws.

---

## SECTION 3: Composition/information on ingredients

### Components

#### 1. Silica, crystalline (airborne particles of respirable size)

Concentration	65 - 75 % (Weight)
Other names / synonyms	Quartz; Sand; Silica, crystalline (airborne particles of respirable size); Silicon (IV) oxide
CAS no.	14808-60-7
H335	May cause respiratory irritation
H350i	May cause cancer by inhalation.
H372	Causes damage to organs through prolonged or repeated exposure

#### 2. Aluminum oxide

Concentration	11 - 13 %
Other names / synonyms	activated Alumina; alpha-Alumina; Alumina; Aluminum oxide; Aluminum oxide (fibrous forms); Aluminum oxide (Powder or Fiber); ALUMINUMOXIDE
CAS no.	1344-28-1

#### 3. Magnesium oxide

Concentration	0 - 1 %
Other names / synonyms	Magnesium oxide
CAS no.	1309-48-4

#### 4. Organic Binders

Concentration	1 - 5 %
Other names / synonyms	Organic Binders

---

## SECTION 4: First-aid measures

### Description of necessary first-aid measures

General advice	Organic portion may be combustible. Dust may cause irritation to eyes, nose, throat, and/or skin.
If inhaled	Move to fresh air and consult with local medical personnel if discomfort persists.

# Safety Data Sheet

## STC Type "B" Glass Coating Slurry

In case of skin contact	Wash affected area with soap and water and consult with local medical personnel if irritation persists.
In case of eye contact	Flush with tepid water for a minimum of 15 minutes and consult with local medical personnel if discomfort persists.
If swallowed	Administer water to dilute, but not if person is unconscious. Consult with local medical personnel if discomfort persists.

---

### SECTION 5: Fire-fighting measures

#### Suitable extinguishing media

Use any means suitable for extinguishing surrounding fire.

#### Specific hazards arising from the chemical

Possible Class A fire hazard – combustible vapors can develop in the headspace over the product. Flash point is 220°C (428°F).

#### Special protective actions for fire-fighters

Use protective clothing and breathing equipment appropriate for the surrounding fire and to protect against the dust that may be dispersed in the air.

---

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Any dust from machining should be wet mopped or dry vacuumed. Liquid glaze should not be ingested and any contact with eyes or mucous membranes should be dealt with using a water flush as required.

#### Methods and materials for containment and cleaning up

Any dust from machining should be wet mopped or dry vacuumed. Liquid spills should be wet mopped or contained using water and disposed of in accordance with local laws

---

### SECTION 7: Handling and storage

#### Precautions for safe handling

Store in a cool dry place. Any dust should be sponge mopped.

---

### SECTION 8: Exposure controls/personal protection

#### Control parameters

##### 1. Silicates (less than 1% crystalline silica), Soapstone, respirable dust

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

##### 2. Silicates (less than 1% crystalline silica), Soapstone, respirable dust

PEL (Inhalation): See Annotated Z-3 mg/m<sup>3</sup> (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

##### 3. Silicates (less than 1% crystalline silica), Soapstone, respirable dust

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)

# Safety Data Sheet

## STC Type "B" Glass Coating Slurry

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 4. Silicates (less than 1% crystalline silica), Soapstone, respirable dust

REL (Inhalation): See Annotated Z-3 (NIOSH)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 5. Magnesium oxide fume - Total Particulate (CAS: 1309-48-4)

PEL (Inhalation): 15 mg/m<sup>3</sup> (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 6. Magnesium oxide fume - Total Particulate (CAS: 1309-48-4)

PEL (Inhalation): 10 mg/m<sup>3</sup> (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 7. Magnesium oxide fume - Total Particulate (CAS: 1309-48-4)

REL (Inhalation): See Appendix D (NIOSH)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 8. alpha-Alumina (CAS: 1344-28-1)

PEL (Inhalation): see PNOR (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 9. alpha-Alumina (CAS: 1344-28-1)

REL (Inhalation): See Appendix D (NIOSH)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 10. alpha-Alumina, Total dust (CAS: 1344-28-1)

PEL (Inhalation): 15 mg/m<sup>3</sup> (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 11. alpha-Alumina, Total dust (CAS: 1344-28-1)

PEL (Inhalation): 10 mg/m<sup>3</sup> (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 12. alpha-Alumina, Respirable fraction (CAS: 1344-28-1)

PEL (Inhalation): 5 mg/m<sup>3</sup> (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 13. alpha-Alumina, Respirable fraction (CAS: 1344-28-1)

PEL (Inhalation): 5 mg/m<sup>3</sup> (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### Appropriate engineering controls

Local or general exhaust ventilation recommended.

### Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Safety goggles in the presence of airborne dust.

#### Skin protection

Polymer gloves for prolonged dust exposure.

#### Respiratory protection

NIOSH/MSHA approved respirator for dust when exposure limit is exceeded.

#### Thermal hazards

CO and CO<sub>2</sub> in a fire and at temperatures >220°C (428°F).

---

## SECTION 9: Physical and chemical properties

# Safety Data Sheet

## STC Type "B" Glass Coating Slurry

### Information on basic physical and chemical properties

Appearance/form	Blue or Tan Liquid
Odor	Odorless
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A
Initial boiling point and boiling range	N/A
Flash point	N/A
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper/lower flammability limits	N/A
Upper/lower explosive limits	N/A
Vapor pressure	N/A
Vapor density	N/A
Relative density	>1.5 g/cc
Solubility(ies)	Organic Portion Soluble in Water
Partition coefficient: n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

---

## SECTION 10: Stability and reactivity

### Chemical stability

Stable

### Hazardous decomposition products

CO and CO<sub>2</sub> in a fire and at temperatures >220°C (428°F).

---

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Respiratory or skin sensitization

See Section 2

#### Carcinogenicity

See Section 2

#### STOT-repeated exposure

See Section 2

---

## SECTION 12: Ecological information

No Applicable Information Found

---

## SECTION 13: Disposal considerations

Disposal of the product

# Safety Data Sheet

## STC Type "B" Glass Coating Slurry

This material is not hazardous per 40 CFR 261. Consultation with federal, state and local officials is recommended before disposal.

---

### SECTION 14: Transport information

**DOT (US)**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

---

### SECTION 15: Regulatory information

**US FEDERAL****TSCA**

CAS# 1344-28-1 is listed on the TSCA inventory.

CAS# 1309-48-4 is listed on the TSCA inventory.

CAS# 14808-60-7 is listed on the TSCA inventory.

**SARA Section 302 Extremely Hazardous Substances**

None of the chemicals in this product have a TPQ.

**Section 313**

CAS# 1344-28-1 is reported under Section 313.

**OSHA:**

None of the chemicals in this product are considered highly hazardous by OSHA.

**US STATE**

**CAS# 1344-28-1** can be found on the following state right to know lists:

Illinois, Minnesota, Massachusetts, New Jersey, Pennsylvania, Texas.

**CAS# 1309-48-4** can be found on the following state right to know lists:

Illinois, New Jersey, Pennsylvania, Texas (regulated under a synonym)

**CAS# 14808-60-7** can be found on the following state right to know lists:

Massachusetts, Pennsylvania, Texas.

Consult your state and local resources for further information.

**California Prop 65**

Crystalline Silica (airborne particles of respirable size) is classified as a substance known to the state of California to be a carcinogen.

---

### SECTION 16: Other information

**Further information/disclaimer**

Although reasonable care has been taken to provide accurate and current information in preparation of this document, Superior Technical Ceramics extends no warranties, makes no representation and assumes no responsibility for any loss, damage, or injury of any kind which may result from reliance of information provided in this document by any person.

**Preparation Information**

Prepared by: Superior Technical Ceramics

1-802-527-7726

lab@ceramics.net

**Safety Data Sheet**  
**STC Type "B" Glass Coating Slurry**

Prepared on: June 1, 2015  
Last Revision: --